




HSF RoHS

SPECIFICATIONS
PERFORMANCE

Electical Rating:AC/DC 50V 0.5A
 Insulation Resistance: 500MΩ
 Contact Resistance:30mΩ Max
 Withstang Volt:200V AC/minute
 Opratng Temperature:-40℃ to +105℃
 Contact Material:Phosphor Bronze
 Plating:Au or Sn over Ni
 Insulation Material:PA46
 Max.Processing Temp:260°C±5°C 5S


Dimension Table		
No Of Pins	Dim A	Dim B
20	7.20	4.50
30	9.70	7.00
32	10.20	7.50
36	11.20	8.50
40	12.20	9.50
50	14.70	12.00
60	17.20	14.50
80	22.20	19.50
100	27.20	24.50




Ordering Information

3720 F XXX 023 XX X X 0X

F=Female
M=Male
No.of pins 20~100P
Plastic Height 023=2.3mm
Contact Plating
G1:Gold Flash
G2:1.5U" Gold
G3:2U" Gold
G4:3U" Gold
G5:5U" Gold
S0:Gold Flash/Tin
Insulator Material Option
C=BK-PA6T
D=BK-PA46
F=BK-LCP
Packing
T=Tube
R=Reel



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)



				OPERATION		DRAW	Jelly Feng	22.11.01	SCALE	FIT	JILN ® 深圳市锦凌电子有限公司 SHENZHEN JINLING ELECTRONICS CO.,LTD Tel: 86-755-27483253 Fax: 86-755-2997-5588	
				X.X	±0.30							
				X.XX	±0.20	APPROVE			SIZE	A4	PART NO.	3720FXXX023XXXX0X
				X.XXX	±0.10							
A0	2022.11.01	NEW DRAWING		Angle	±3°	PROJ.	TITLE:	0.5BTB-NPIN H=2.3母座无柱无定位片				
REV	DATE	MODIFICATION DESCRIPTION		DIM	TOL							